



	Description	Description	Descripcion
→ Nominal Ø	Ø 50mm		
→ Tête / shoulder / cabeza	à vis	standard screw on	de rosca estandar
→ Cap	Capsule tambour D.50	Full diameter screw on Cap	Tapon de rosca D. 50mm
→ Ref	50SC050SS		

	Décor	Decoration	Cabeza
→ Offset	6 Clichés : Max. 6 couleurs. Impression jusqu'à l'épaule. Trame résolution 130dpi Intensité min.5%	6 printing plates = Max. 6 color, Printing up to the neck. Half tone 130dpi, 5% min.	6 Cliches : Max 6 colores, Impression hasta el hombro. Tramado 130 dpi, 5% minimo
→ Sérigraphie/Screen printing / sérigrafia	6 écrans : Max. 6 couleurs	6 screens : Max 6 colors	6 pantallas : Max 6 colores
→ Marquage à Chaud / Hot stamping / Estampacion	Or et argent Brillant standard et films standards pour tubes disponibles en catalogue.	Gold and silver Glossy standard shades + Other shades as per suppliers' catalogue	Oro y plata brillante estandar asi que todos colores disponibles con nuestros proveedores
→ Vernis / Lacquer / Varnizado	Brillant / Mat / Satiné	Glossy / Mat / Satin	Brillante / Mate / Satin

	Juqe	Sleeve	Falda
→ Process	Extrusion Monocouche	Monolayer Extrusion	Extrusion Monocapa
→ Material	PE -HD /BD /BDL et compounds	HD / LD / LLD -PE and blends	PE -HD /BD /BDL y mezclas
→ Color	Tous Colorants sur base PE	All Masterbatches on PE Basis	Todos colorantes en base PE
→ ext diameter		50mm +/- 0,3	
→ Int diameter		49mm +/- 0,3	
→ Min L		100mm +/-1,5	
→ Max L		180mm +/- 1,5	
	Longueur de juqe Standard	Standard Sleeve Length	Altura de falda estandar
	125ml	115mm	
	150ml	130mm	
	200ml	155mm	
	250ml	180mm	

	Tête	shoulder/tip	Cabeza
→ Filet /Thread /rosca	KS 22 x 3,0	KS 22 x 3,0	KS 22 x 3,0
→ Process	Injection	Injection molding	Inyeccion
→ Material	PEHD	HDPE	PEHD
→ Color	Tous Colorants sur base PE	All Masterbatches on PE Basis	Todos colorantes en bases PE
→ Orifices	3,5mm, 5,5mm +/-0,2mm		
→ Opercule / Foil tab / Operculo	Alu/PE	Alu/PE	Alu/PE

	Capsule	Cap	Tapon
→ Name	Capsule tambour D.50mm	Standard screw on cap D.50	Tapon de rosca estandar D.50mm
→ Process	Injection	Injection molding	Inyeccion
→ Finish	Brillant	Glossy	Brillante
→ Material	PP homo		
→ Color	Tous Colorants sur base PP	All Masterbatches on PP basis	Todos colorantes en base PP
→ Diametre		48,5mm +/-0,2	
→ Hauteur / Height / Altura		26,8mm +/-0,2	
→ Orifices / Orificios	N/A		
→ Etanchéité / Tighness / estanqueidad	A plat et/ou picot	Flat seal and/or pintle	Plana
→ P. Injection/ gate/ inyeccion	Central exterior sans lunule	Central external – No dimple	central exterior sin lenteja
→ Charnière / Hinge / Bisagra	N/A	N/A	N/A
→ Inv iolabilité / Tamper evidence / inv iolabilidad	N/A	N/A	N/A
→ Decoration	Marquage à Chaud	Hot stamping	Estampacion